MICRO CENTRIFUGE

MICRO HEMATOCRIT CENTRIFUGE

DSC-100MH Series

DSC-100MH-1

DSC-100MH-2

DSC-100MH-3

Features:

* Micro hematocrit centrifuge is an indispensable instrument in laboratory.
* Auto-balancing system can extend motor life and reduce noise.
* With safety switch, when lid is lifted during operation, the rotor will stop spinning.
* Good ventilation system prevents the motor from overheating.
* Precision timer with bell can be set from 0 to 15 minutes.
* Manual brake can faster control over the spin down cycle.
* There are three models available.
  (1) Model DSC-100MH-1 with clear lid, metal top and ABS plastic bottom is your economic choice.
  (2) Model DSC-100MH-2 with all metal housing is heavy duty.
  (3) Model DSC-100MH-3 with all metal housing and inner stainless steel chamber can make operation quietly.
* Quality certification: ISO 9001, CE

Specifications for DSC-100MH series:

Model	Motor	Rotor	Timer (min.)	Standard Accessory	Weight (kg) (N.W. / G.W.)	Size (mm) (W×D×H)
DSC-100MH-1	Universal motor	HT-24	0~15 min. mechanical timer	Percentage reader	4.5 / 5.0	220×240×200
DSC-100MH-2					9.0 / 9.5	300×300×240
DSC-100MH-3					13.0 / 14.0	320×355×255

Power Supply: AC110V 60Hz (220V 50/60Hz available)

Specifications of rotor:

Model	Speed (rpm)	Type	Max. R.C.F. (g-force)	Capacity
HT-24	12,000 (fixed)	Disc	14,810	Capillary tubes (Φ 1.5 x 75mm) x 24

Rotor HT-24

Standard percentage reader (aluminum) for rotor HT-24

Optional wax for capillary tube

Optional capillary tube for rotor HT-24; size: Φ1.5x75mm

Optional disc percentage reader (plastic) for rotor HT-24

Aron Laboratory Instruments Inc.

Tel:886-2-7708-6789
Fax:886-2-7708-6799
http://www.aron.com.tw