ROTATOR / SHAKER

ROTATOR

DSR-Series

DSR-2100V DSR-2100A DSR-2800V DSR-2800A

Features:

* Widely used in VDRL, PRP, and EIA test.
* Stable and quiet operation.
* With variable speed, timer control, and continuous operation.
* Quality certification: ISO 9001

Specifications:

Model	DSR-2100V	DSR-2100A	DSR-2800V	DSR-2800A
Speed	40 ~ 240rpm			
Timer	0~30 min. mechanical timer			
Tachometer	No	Yes	No	Yes
Platform size (mm) (W×D)	230×230		280×280	
Orbit diameter	20mm			
Load capacity	0.5 kg			
Standard accessory	1 pc of spring			
Size (mm) (W×D×H)	230×230×150	230×230×150	280×280×150	280×280×150
Weight (kg) (N.W. / G.W.)	4.3 / 5.1	4.5 / 5.3	5.3 / 6.0	5.3 / 6.0

Power Supply: AC110V 60Hz (220V 50/60Hz available)

ORBITAL SHAKER

OS-Series

OS-500 with flat platform

OS-500 with clamps

Features:

* Designed for continuous-operation orbital shakering, day and night, year in and year out.
* Suitable for carrying heavy duty.
* Maintenance-free induction brushless motor.
* Differential clamps available.
* All stainless steel platform and clamps.
* Quality certification: ISO 9001

Capacity for flasks:

Model \ Item	50 ml	125 ml	250 ml	500 ml	1000 ml	2000 ml	3000 ml	5000 ml
OS-340	48	35	20	12	6	2	1	1
OS-500	80	48	30	12	9	4	4	4
OS-600	80	48	30	20	12	6	6	4
OS-1060	160	96	60	40	24	12	12	8

Specifications:

Model	OS-340	OS-500	OS-600	OS-1060
Speed	10 ~ 250rpm			
Platform size (mm) (W×D)	340×340	500×500	600×480	1060×600
Orbit diameter	25mm			
Size (mm) (W×D×H)	380×410×195	560×600×225	660×580×225	1120×700×225

Power Supply: AC110V 60Hz (220V 50/60Hz available).

Note: Max. speed 450rpm available upon request.

Aron Laboratory Instruments Inc.

Tel:886-2-7708-6789
Fax:886-2-7708-6799
http://www.aron.com.tw